



AIR SOLUTIONS
~ A S I A ~

25 Ubi Road 4, #02-00 Weltech Building, Singapore 408621. Tel: 6781 1468 Fax: 6846 9690

Model ASA-18-CENTRIFUGAL Series - Detailed Product Description

1. Super energy saving, it requires only 1.5kw per hour to cool a 100-150m² factory
2. Single-phase 220V input. With touch screen, remote and inverter controller with 12 stage speed adjusting.
3. Three-phase 220V copper-wire motor with heavy cast iron cabinet, starting and running smoothly, anti-corrosion of acid and alkali.
4. Automatically protect for over current/voltage, lack current/voltage and water shortage. Self cleaning function
5. Direct connection type of centrifugal fan with high hydrostatic pressure ,low noise and long delivery distance, particularly suitable for commercial places which requires little noise
6. With extra thick and firm CO-PP plastic cabinet, age inhibiting ,never rust ,long life duration
7. With high quality evaporative filter cooling pad, good effect of evaporating and reducing temperature, easy to clean, edge binding protected and durable
8. Open-type hard water pipe along with water distribution system ensures spraying water evenly and smoothly
9. Different design of up outlet, down outlet and side outlet can meet various engineering needs of the environment
10. With super silent wind pipe which is specially used for internet bar, offices, supermarket, carparks, etc

Centrifugal and inverter ASA-18-CT/CS/CB model parameters are as follows

Maximum airflow	Max .air pressure	Volt/Fre	Power	Speed	Fan	Size	Approx. Weight
(m3/h)	(pa)	(V/HZ)	(KW)			(LxWxH)(mm)	(KG)
18000	300	380/50	1.5	Single	Centrifugal	1100x1100x1000	110

Area	Wind distance	Air outlet dimension	Water container	Controller	Noise	Air discharge outlet
(m2)	(m)	(mm)	(L)		(db)A	
100-150	40	variable, depends on model	25	Touch screen	<=83	Top / Side / Bottom



Model ASA-18-Centrifugal Series

- MODEL ASA-18-CT - Top air outlet**
- MODEL ASA-18-CS - Side air outlet**
- MODEL ASA-18-CB - Bottom air outlet**